



Photo Controls

Stem Mounting, Thermal Type — K4100 Series

This series features single and multivolt models in both stem mount and stem mount with a swivel. All models are equipped with a light level slide adjustment and provide a 1/2"-14 threaded stem. A washer gasket and locking nut are packaged with each photo control. Models with "M" suffix have heavy duty die cast housings. Model K4251 and K4253 have photo eye located on top and are designed for spot/flood type fixtures.

Size – K4100 Series - 1-9/16" (4.0 cm) Square, 3" (7.6 cm) Long;
 K4200 Series - 1/2"-14 threaded swivel, 1-9/16" (4.0 cm) Square, 5-1/2" (14.0 cm) Long;
 Model K4236 - 5-3/4" (14.6 cm) High, 3" (7.6 cm) Diameter.

| Model # | Watts Tungsten | VA Ballast | Amps Tungsten | Amps Ballast | Volts |
|-----------|----------------|------------|---------------|--------------|------------|
| K4121C | 1800 | 1000 | 15 | 8.3 | 120 |
| K4121M | 2000 | 1800 | 16.7 | 15 | 120 |
| K4421M | 1800 | 1000 | 15 | 8.3 | 120 |
| K4124 | 3100 | 1700 | 15 | 8.3 | 208 |
| K4122 | 3600 | 2000 | 15 | 8.3 | 240 |
| K4123C | 3100-4150 | 1700-2300 | 15 | 8.3 | 208-277 |
| K4423M*** | 3100-4150 | 1700-2300 | 15 | 8.3 | 208-277 |
| K4133 | 4150 | 2300 | 15 | 8.3 | 277 |
| K4127**** | 5205 | 2880 | 15 | 8.3 | 347 |
| K4135* | 7200 | 4000 | 15 | 8.3 | 480 |
| K4136M | 2000-4625 | 1800 | 16.7 | 8.6 | 120 or 277 |
| **K4141C* | 3000 | 3000 | 25 | 25 | 120 |

* Not UL listed or CSA certified.
 ** 1 year warranty.
 *** Model K4423M replaces K4123M
 **** Certified by CSA to US and Canadian Standards.



K4121C



K4121M



K4423M



K4221C



K4236C



K4251

Stem & Swivel Mounting, Thermal Type — K4200 Series

| Model # | Watts Tungsten | VA Ballast | Amps Tungsten | Amps Ballast | Volts |
|----------|----------------|------------|---------------|--------------|----------------|
| K4221C | 1800 | 1000 | 15 | 8.3 | 120 |
| K4224 | 3100 | 1700 | 15 | 8.3 | 208 |
| K4222 | 3600 | 2000 | 15 | 8.3 | 240 |
| K4223C | 3100-4150 | 1700-2300 | 15 | 8.3 | 208-277 |
| K4233 | 4100 | 2300 | 15 | 8.3 | 277 |
| K4227*** | 5205 | 2880 | 15 | 8.3 | 347 |
| K4235* | 7200 | 4000 | 15 | 8.3 | 480 |
| K4236C | 1800-4150 | 1000-2300 | 15 | 8.3 | 120 or 208-277 |
| K4251*** | 1800 | 1000 | 15 | 8.3 | 120 |
| K4253*** | 3100-4150 | 1700-2300 | 15 | 8.3 | 208-277 |

* Not UL listed or CSA certified.
 *** Certified by CSA to US and Canadian Standards.



C22.2-177
LR3730