



Short Range Cycle Timer

Short Range Cycle Timers provide repeat cycling for "ON" times. Ten combination "ON/OFF" trippers supplied with each switch.

Applications

- Ventilating Fans
- Spraying Equipment
- Livestock Feeders
- Poultry Fans
- Fogging Equipment
- Poultry Feeders
- Pumps
- Bulk Milk Coolers
- Process Equipment

Specifications

Case – Same as T100 Series.

Knockouts – Same as T100 Series.

Optional Enclosures – Same as T100 Series.

Switch Rating – 20 Amp Resistive 125, 208-277 VAC; 1/2 HP, 125 VAC; 1 HP, 250 VAC

Model #	Switch	Clock Motor Volts 60 Hz	Dial Cycle	Tripper Actuating Time	Amps
C8815	SPDT	125	10 Min.	5 Sec.	20
C8835	SPDT	125	30 Min.	15 Sec.	20
C8865	SPDT	125	1 Hr.	30 Sec.	20
C8845	SPDT	125	4 Hr.	120 Sec.	20
C8866	SPDT	250	1 Hr.	30 Sec.	20

Note: The life of the switch contacts is affected by the size and type of the controlled load. The expected minimum life at 20 amps (resistive) load is 100,000 cycles.

Replacement Snap Switch 133T773A.

For additional trippers (12 trippers per pack), order No. 156T1950A.



C22.2-177
LR3730
UL917



2.75 lbs
1.25 kg



-40°F
(-40°C)
to
130°F
(54°C)