

Photocontrol - ANSI C136.10 Locking Type NEMA Receptacle, (30" lead), gasket included

Item K121-30



PRODUCT DESCRIPTION

The K121 NEMA receptacles provide the connector interface for locking type photocontrols. They can be installed in the light fixture itself (K121), or attached externally with the use of a mounting bracket (K122).

FEATURES

- ▶ NEMA receptacle with 3-prong sockets
- ▶ Compliant to ANSI C136.10 specifications

APPLICATIONS

- ▶ Parking Lots
- ▶ Landscape Lighting
- ▶ Exterior Lighting
- ▶ Pedestrian Pathway Lighting
- ▶ Street Lighting

TECHNICAL DATA

General

Model Number	K121-30
Description	ANSI C136.10 Locking Type NEMA Receptacle, (30" lead), gasket included
UPC Code	078275107175
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty	1-Year limited

Dimensions

Product Height (in)	1.52
Product Height (mm)	38.6
Product Diameter (in)	2.55
Product Diameter (mm)	64.7

Material Specifications

Color	Black
Base Material	Phenolic
Power Contacts Material	Brass/Phosphor Bronze
Gasket	(Integrated) Thermal Elastomer
Wire Leads	#14 AWG, 105°C, AWM3321

Electrical Specifications

Power Contacts Rating	480 V max, 15 A max
-----------------------	---------------------

Packaging

Shipping Weight (lbs)	0.251
Unit Carton Height (in)	2.251

Environmental Specifications

Temperature (operation) -40°C..80°C

Standards and Certifications

CSA Certification	CSA C22 No. M1986
Other Certifications and Compatibilities	CA Title 20; cRUus; Ansi C136.10
UL Standard	UL 772
California Proposition 65	DEHP

ACCESSORIES



K121-GSKT
Gasket for K121