

Model: P36 Series

360 kA Per Phase*
ANSI/UL 1449

Type 1 SPD (no filter), $I_n = 20$ kA
Type 2 SPD (filter), $I_n = 20$ kA



* Based on 3 Phase Wye, 4 Wire and Ground
 I_n = Nominal Discharge Current per ANSI/UL 1449

Key Features

- **Discrete “All Mode” Circuitry: Directly Connected Protection Elements in “All Modes” (10 modes for 3 phase Wye circuits) as recommended by ANSI/IEEE Std. 1100-2005**
- **Industry Leading Measured Limiting Voltage (let-through) Performance**
- **Multi-stage Hybrid Frequency Responsive Circuitry**
- **Local & Remote Diagnostics**
- **Independent Verification of Performance and Safety**
- **No moving parts or springs - No mechanical or electro-mechanical thermal/over-current protection**
- **Component-Level, Thermal Fusing**
- **Patented Internal, Circuit Board Mounted, Over-Current Fusing**
- **25 Year Unlimited Free Replacement Warranty**



PANELGUARD® INTERMATIC®

Application: The P36 series was developed to answer a broad variety of demands from our customers. This device is robust enough to handle the punishment of service entrance applications while providing protection from transients that are generated inside their facility. The constant bombardment of this combination of transients can damage valuable equipment and waste budget dollars.

ANSI/IEEE C62.41.1 & C62.41.2-2002 environments: Suitable for Categories: A, B & C (Most Severe Electrical Environments)

IEC Environments: Suitable for use in IEC 61643-11 environments

Circuit Topology: Parallel configured combination **Frequency Responsive Circuitry** and **Voltage Responsive Circuitry** circuit design incorporating component-level, thermal fusing and circuit board mounted, **Patented** internal over-current fusing methodology with discrete **“All Mode”** protection (10 modes for 3 phase Wye units). All protection circuits are encapsulated in our high-dielectric compound to promote long component life and protection from the weather and vibration.

Protection Modes: Industry-best practice of dedicated protection components for all operational modes of the electrical system. **Discrete L-N, L-L (Normal Mode) and L-G, N-G (Common Mode)** Example: Directly Connected Protection Elements in All 10 modes for a 3 phase, 4 wire, Wye system, (i.e., 3 L-N modes, 3 L-L modes, 3 L-G modes and 1 N-G mode).

Input Power: 50-60 Hz (60 Hz nominal)

Temperature Rating: Up to 80°C

Insertion Loss Data: (L-N)

Frequency:	10 kHz	100 kHz	1 MHz	Max Attenuation & Freq.
Attenuation:	20 dB	52 dB	21 dB	55 dB @ 106 kHz

Standard Enclosure: NEMA 4x rated composite enclosure

Nominal Discharge Current (I_n) Rating: 20 kA

(*Complies with the requirements of UL 96A Master Label for Installation Requirements for Lightning Protection Systems)

Diagnostics: Blue LED's, one per phase, normally on. A wide range of optional diagnostics is available (see page two for details).

Circuit Interrupt: Internal component-level, thermal fusing and patented circuit board mounted over-current fusing. No external over-current protection required. Note: National and local codes may require the use of a circuit interrupt device(s) if conduit is added to make the wired connection to the panel or gear.)

Short Circuit Current Rating: 200 kAIC

Product Qualifications:

Listed to ANSI/UL 1449 by UL (E340498), CSA (MC#241804); UL1283

Voltage Code	ANSI/UL 1449 Voltage Protection Rating (VPR)						
	L-N	HL-N	L-G	HL-G	N-G	L-L	HL-L
1S1	600	-	600	-	600	1000	-
3Y1	600	-	600	-	600	1000	-
3D1	600	1000	600	1000	600	1000	1000
3Y2	1000	-	1000	-	1000	1800	-
3N2	-	-	1000	-	-	1000	-
3N4	-	-	1800	-	-	1800	-

Intermatic Incorporated
1950 Innovation Way, Suite 300 Libertyville, IL 60048
www.intermatic.com 815-675-7000

© 2023 Intermatic®. Rev Date 6/2023

Page 1 of 2

Voltage Code*	Circuit Type	Peak Surge Current	MCOV	ANSI/IEEE C62.41.2™-2002, C62.45™-2000 and C62.62™-2010 Measured Limiting Voltages (tested with 6 inches of lead length external to the enclosure per C62.62™-2010 and ANSI/UL 1449)		
				Test Mode	Cat A, 30 Ω 100 kHz Ring Wave 2 kV / 67 A @ 270° Phase Angle	Category C (High) 10 kA 8/20 Current Driven Test†
1S1	120/240 V 1Ø (Split) (3 wire + ground)	120 kA L-N	150 V	L-N	22 V	729 V
		120 kA L-L	300 V	L-L	38 V	964 V
		120 kA L-G	150 V	L-G	60 V	781 V
		120 kA N-G	150 V	N-G	60 V	991 V
		720 kA Total	150 V			
3Y1	120/208 V 3Ø Wye (4 wire + ground)	120 kA L-N	150 V	L-N	22 V	729 V
		120 kA L-L	300 V	L-L	38 V	964 V
		120 kA L-G	150 V	L-G	60 V	781 V
		120 kA N-G	150 V	N-G	60 V	991 V
		1,200 kA Total	150 V			
3D1	120/240 V 3Ø High-Leg Delta (4 wire + ground)	120 kA L-N	150 V	L-N	22 V	729 V
		120 kA HL-N	320 V	HL-N	28 V	1,374 V
		120 kA L-L	300 V	L-L	38 V	964 V
		120 kA L-G	150 V	L-G	60 V	781 V
		120 kA HL-G	320 V	HL-G	51 V	1,414 V
		120 kA N-G	150 V	N-G	60 V	991 V
		1,200 kA Total	150 V			
3Y2	277/480 V 3Ø Wye (4 wire + ground)	120 kA L-N	320 V	L-N	28 V	1,374 V
		120 kA L-L	550 V	L-L	102 V	1,758 V
		120 kA L-G	320 V	L-G	76 V	1,414 V
		120 kA N-G	320 V	N-G	53V	1,661 V
		1,200 kA Total	320 V			
3N2	240 V 3Ø Delta (NN) (3 wire + ground)	120 kA L-L	320 V	L-L	38 V	964 V
		120 kA L-G	320 V	L-G	1038 V	1,414 V
3N4	480 V 3Ø Delta (NN) (3 wire + ground)	120 kA L-L	550 V	L-L	104 V	1,758 V
		120 kA L-G	550 V	L-G	1,559 V	2,071 V

Measured Limiting Voltage (MLV) Test Parameters: Positive polarity, Category A: Line power applied, Category C: No line power applied, Voltages are peak (±10%). Measured Limiting Voltages are measured from the insertion point on the sine wave to the peak of the surge for powered tests. Each MLV is the average of all phases within that mode of protection. To duplicate the results, the specified mode of protection must be tested in all phases (except N-G) and averaged together. (Individual mode or shot results may vary by more than 10%). Scope Settings: Time Base = 10 microseconds per division, Sampling Rate = 2.5 Gigasamples/sec, Bandwidth = 400 MHz (200 MHz for Cat C), Probes: Tektronix P5100/P6015A. These settings help to assure MLV results are accurate. **All tests performed with 6" lead length (external to the enclosure), simulating actual installed performance.** The MLVs reported above are certified by Third-Party, Independent Testing. Individual test reports are available upon request.

†The MLV reported for the Category C High, 10 kA 8/20 Current Driven Test is determined by measuring the MLV of one of the fifteen 10 kA impulses impressed through the SPD during the Nominal Discharge Current (In) Test from C62.62™-2010 and ANSI/UL 1449-2006. This is not the MLV recorded during the pre- and/or post-test 6 kV / 3 kA Combination Wave Test used to determine the VPR of the SPD. The VPRs are reported on page 1 of this specification.

*Other voltage configurations may be available. Contact your sales representative for additional assistance.

Model Number Example: P36T23Y2DG3

Base Model:	Modes of Protection:	Advanced Filtering:	Voltage Codes:	Options:
P36 = 360 kA	T = Ten	1=No Filter 2=Filter	See Voltage Codes 3Y2	See Option codes DG3

- DG1 = Blue LED's, one per phase, normally ON
- DG2⁽¹⁾ = DG1 package plus: Audible internal alarm, Form C relay with External wires.
- DG3⁽¹⁾ = DG2 package plus: surge counter with reset button
- DG4⁽¹⁾ = DG3 package plus: Panel mount alarm mute and test switches
- ⁽¹⁾ = With Form C Dry Relay Contacts.
- D5 (CSA) = Integral, non-fused disconnect switch (SPD unit mounts inside)
- D6 (CSA) = Same as D5, except no external handle
- LP = Remote LED and overlay kit
- P = Flush Mount Plate

Standard Enclosure = NEMA 4X Composite Enclosure

24 = 24" wire leads

36 = 36" wire leads

48 = 48" wire leads

60 = 60" wire leads

Standard Wire Length = 18" wire leads

Enclosure Dimensions			
Inches (mm)	DG1 Option	DG2-4 Option	D1-4 Option
	No Disconnect	No Disconnect	D5 or D6 Disconnect
A	13.25 (337)	13.25 (337)	24.89 (632)
B	12.50 (318)	12.50 (318)	21.25 (540)
C	7.72 (196)	7.72 (196)	10.24 ⁽²⁾ (260)
D	14.25 (362)	14.25 (362)	27.00 (686)
E	15.21 (386)	15.21 (386)	27.00 (686)
G	13.25 (337)	13.25 (337)	25.75 (654)
H	7.50 (191)	7.50 (191)	14.00 (356)
Type	NEMA 4X Composite		
lbs. (kg)	14.20 (6.44)	14.20 (6.44)	55.47 ⁽¹⁾ (25.16)

⁽¹⁾ This dimension is 11.68 in. (297 mm) when option D5, external disconnect, is selected.
⁽²⁾ The weight is 66.57 lbs. (30.20 kg), when option D5 or D6 is selected.

