

M Series

(15-Year Limited Product Warranty)

7 Mode, SCCR rating of 200kA and In rating of 20kA,
Blue LED Status Indicator Per Phase, Red LED Service Indicator

M24S23Y2DG4D3LP24P

Peak Surge Current per Phase Choices	Modes of Protection S = Seven	SPD Type	Voltage Code/Options	Diagnostic Options	Other Options
M6 = 60 kA	S	1 or 2	1P1 - 120 VAC Single Phase 1P2 - 240 VAC Single Phase 1S1 - 120/240 VAC Split ϕ 3Y1 - 120/208 VAC 3 ϕ WYE 3Y2 - 277-480 VAC 3 ϕ WYE 3D1 - 120/240 VAC High-Leg Delta 3N2 - 240 VAC 3 ϕ 3N4 - 480 VAC 3 ϕ	DG1 - LED Only DG2 - DG1 + Audible Alarm, Dry Relay Contact DG3 - DG2 + Surge Counter DG4 - DG3 + Alarm Mute & Test switches	D1 - External Disconnect for models <240kA D3 - Internal Disconnect for models <240kA D5 - External Disconnect for models \geq 240kA D6 - Internal Disconnect for models \geq 240kA LP - Remote LED kit 24" , 36" , 48" & 60" lead wires, (18" leads standard) P - Flush mounting kit
M8 = 80 kA	S	1 or 2			
M12 = 120 kA	S	1 or 2			
M16 = 160 kA	S	1 or 2			
M20 = 200 kA	S	1 or 2			
M24 = 240 kA	S	1 or 2			
M28 = 280 kA	S	1 or 2			
M32 = 320 kA	S	1 or 2			
M36 = 360 kA	S	1 or 2			
M40 = 400 kA	S	1 or 2			
M44 = 440 kA	S	1 or 2			
M48 = 480 kA	S	1 or 2			
M52 = 520 kA	S	1 or 2			
M56 = 560 kA	S	1 or 2			
M60 = 600 kA	S	1 or 2			

P Series

(15-Year Limited Product Warranty)

10 Mode, SCCR rating of 200kA and In rating of 20kA,
Blue LED Status Indicator Per Phase, Red LED Service Indicator

P48T23Y2DG3D624P

Peak Surge Current per Phase Choices	Modes of Protection T = Ten	SPD Type	Voltage Code/Options	Diagnostic Options	Other Options
P10 = 100 kA	T	1 or 2	1P1 - 120 VAC Single Phase 1P2 - 240 VAC Single Phase 1S1 - 120/240 VAC Split ϕ 3Y1 - 120/208 VAC 3 ϕ WYE 3Y2 - 277-480 VAC 3 ϕ WYE 3D1 - 120/240 VAC High-Leg Delta 3N2 - 240 VAC 3 ϕ 3N4 - 480 VAC 3 ϕ	DG1 - LED Only DG2 - DG1 + Audible Alarm, Dry Relay Contact DG3 - DG2 + Surge Counter DG4 - DG3 + Alarm Mute & Test switches	D1 - External Disconnect for models <240kA D3 - Internal Disconnect for models <240kA D5 - External Disconnect for models \geq 240kA D6 - Internal Disconnect for models \geq 240kA LP - Remote LED kit 24" , 36" , 48" & 60" lead wires, (18" leads standard) P - Flush mounting kit
P12 = 120 kA	T	1 or 2			
P18 = 180 kA	T	1 or 2			
P24 = 240 kA	T	1 or 2			
P30 = 300 kA	T	1 or 2			
P36 = 360 kA	T	1 or 2			
P48 = 480 kA	T	1 or 2			
P60 = 600 kA	T	1 or 2			
P72 = 720 kA	T	1 or 2			
P90 = 900 kA	T	1 or 2			